

Badger® Model IR250B	Brass Irrigation Flow Sensor	Sample Specifications
-----------------------------	-------------------------------------	------------------------------

The flow sensor shall be an in line type with a non-magnetic, spinning impeller (paddle wheel) as the only moving part. The electronics housing shall be glass-filled PPS. The impeller shall be glass-filled nylon or Tefzel® with a UHMWPE or Tefzel sleeve bearing. The shaft material shall be tungsten carbide. The electronics housing shall have two ethylene-propylene O-Rings and shall be easily removed from the meter body. The sensor electronics will be potted in an epoxy compound designed for prolonged immersion. Electrical connections shall be 2 single conductor 18 AWG leads 48 inches long. Insulation shall be direct burial "UF" type colored red for the positive lead and black for the negative lead. The sensor shall operate in line pressures up to 400 psi and liquid temperatures up to 220° F, and operate in flows of ½ foot per second to 15 feet per second with linearity of ± 1% and repeatability of ± 1%. The meter body shall be cast 85-5-5-5 bronze, available in ½", ¾", 1", 1 ¼", and 1 ½" female iron pipe thread sizes. This flow sensor shall be Badger Model IR-250B.

Badger® and Data Industrial® are registered trademarks of Badger Meter, Inc. Tefzel® is a registered trademark of E.I. DuPont de Nemours and Company.

DSS-018-01

4-09



Please see our website at www.badgermeter.com for specific contacts.

Copyright © Badger Meter, Inc. 2009. All rights reserved.

Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists.



BadgerMeter, Inc.

6116 E. 15th Street, Tulsa, Oklahoma 74112
(918) 836-8411 / Fax: (918) 832-9962

www.badgermeter.com